CP20

Touchscreen control for connected teams.

An Android push-to-talk terminal with a 2.4-inch touchscreen, cameras, dual SIM slots and a 2W speaker. Select users and groups on screen and connect through cellular or Wi-Fi networks.



Touchscreen control

2.4-inch TFT touchscreen for channel, signal and battery information, and selecting users and groups.

Cellular and dual-band Wi-Fi

Dual Micro SIM slots and 2.4 GHz / 5 GHz Wi-Fi. Automatic SIM failover is not confirmed.

Audio, cameras and positioning

2W speaker, 5MP and 2MP cameras, Bluetooth 4.2 and GNSS positioning.

Operational durability

IP65 standard, IP67 optional, with a stated 1.2 m drop test. Weight: 257 g.

Standard accessories: Li-ion battery, USB cable, desktop charger, belt clip and instruction manual.

One Click Away IT Solution LLC
+971 55 602 7771 | support@1clickaway.xyz
ocaitsolutions.com | Abu Dhabi, United Arab Emirates

Device specifications

Operating system	Android
Processor	Quad-core, 1.3 GHz
Memory	1 GB RAM + 8 GB ROM
Display	2.4-inch TFT LCD touchscreen
Control	Dedicated PTT button
Loudspeaker	2W
Cameras	5MP + 2MP
SIM	Dual Micro SIM
Wi-Fi	802.11 a/b/g/n; 2.4 GHz and 5 GHz
Bluetooth	4.2
Dimensions	134 x 65 x 23.5 mm
Weight	257 g
Protection	IP65 standard; IP67 optional
Drop test	1.2 m
Interfaces	Micro USB 2.0; M6 earphone jack
Positioning	GNSS
Battery	3500 mAh
Operating temperature	-20 to +55 degrees C
Storage temperature	-30 to +70 degrees C
GSM bands	B2 / B3 / B5 / B8
FDD-LTE bands	B1 / B3 / B5 / B7 / B8 / B20 / B28A-B
TDD-LTE bands	B38 / B39 / B40 / B41

Specifications follow the supplied device datasheet and may vary by hardware version. Network coverage, battery runtime and indoor positioning require site validation. Optional features, software functions, licences, installation and warranty/service coverage are defined in the commercial proposal.